

# **GENERAL INFORMATION**



### **STANDARD FEATURES**

- 16 gauge #304 stainless steel countertop
- 18 gauge #304 stainless steel trim
- · 6" casters, two (2) rigid and two (2) swivel with brakes
- Black rubber caster skirt on three (3) sides
- · Black vinyl bumper on three (3) sides
- Powder coated exterior panels (red, blue or yellow)
- Electrical compartment
- Locking storage compartment
- Drop-in ice bin with hinged and locking lid
- Drop-in hand sink with faucet (single bowl)
- BSI DECO-204 food guard
- Stainless steel round retractable awning poles
- A-Frame awning with fabric covering (red, blue or yellow)
- Track lighting
- All tanks, valves, piping and fittings to comply with all NSF, local, state and federal health codes and standards
- U.L. Listed
- NSF Listed to Standard 59

# **OPTIONS**


- □ Vinyl bumper colors
- □ Square awning poles
- Fixed awning poles
- Drop shelf
- □ Round awning
- Custom exterior panels (laminate, stainless steel, powder coat, etc.)
- Custom colors
- Custom graphics
- Menu board
- □ Spot lights
- Recessed canister lights
- Cart cover


### **ELECTRICAL REQUIREMENTS**

120/208 Volt / 1 Phase / 50 Amp

# **CUSTOM SMOOTHIE CART**

8' Cart





All fixtures and equipment to be connected to a single load center. Cart to have one (1) 8' power cable with a NEMA 14-50P plug.

#### **PLUMBING PROVIDED**

- One (1) 5-1/2 gallon fresh water tote tank
- One (1) 7-1/2 gallon waste water tote tank
- One (1) water pump
- One (1) 2-1/2 gallon hot water heater
- One (1) 2-compartment stainless steel hand sink with two (2) 6-1/8" x 12-1/8" x 5" deep bowls

Fresh and waste water tanks to be accessible from operator side and are removable with quick disconnects for ease of cleaning.

Water heater to deliver water to hand sink between a minimum of  $80^{\circ}$ F and a maximum of  $120^{\circ}$ F.

The ice bin to drain to the same 7-1/2 gallon waste tank as the sink.

Specifications subject to change without notice.